

### **Technical Data Sheet**

# Adensa NVH 6013 Compound

Filled Heavy Layer Acoustic Barrier Compound

**Description** Adensa 6013 is a low fog filled thermoplastic ethylene copolymer that provides acoustical

sound barrier performance in automotive, construction, and industrial applications.

**Applications** Sheet extrusion for NVH applications

**Key Benefits** Designed as an acoustic barrier, and formulated for thermoforming and die cutting

Pthalate-free alternative to Mass Loaded Vinyl (Filled PVC)

**Forms** Pelletized compound

• 1,000 lb. container, 3' x 3' x 5'

**Appearance Black** 

Nominal **Property** Method **Typical Properties\*** 

.17		
Ash Content	74.3 %	ASTM D5630
Moisture Content	0.04 %	ASTM D6980
Melt Index	3.30 g/10min	ASTM D1238
Specific Gravity	2.01	ASTM D792
Tensile Strength, Br	338.3 PSI	ASTM D638
Tear Strength, Br	124.3 lb-f/in	ASTM D642
Elongation, Br	NB; >300%	ASTM D792

Adhesion & Adensa 6013 is a polar material and can be extruded and laminated to most substrates

Lamination without additional corona or flame treatment.

**Processing** Value (English) Value (SI)

> 360 - 400 °F 182 - 204 °C **Extrusion Temp Forming Temp** 220 - 240 °F 104 - 115 °C

Please contact your Highland Sales Representative to request regulatory information and safety data sheet.

Information

The information contained in this document is for informational purposes only and should not be used as a substitute for testing to ensure that this product is suitable for its intended use. It is the sole responsibility of the user to determine the suitability of this product for the uses and applications intended by the user or others, to ensure compliance with all federal, state, and local laws, rules, and regulations, and to obtain all necessary certifications, permits, and authorizations. All products supplied by Highland Plastics, Inc. or any of its affiliates or subsidiaries are subject to Highland Plastics, Inc.'s terms and conditions of sale. Highland Plastics does not make, and expresssly disclaims, any warranty, express or implied, concerning the product, including the merchantability or fitness of the product for any particular purpose, or concerning the accuracy of any information provided herein. Nothing contained herein constitutes an offer for the sale of any product.





## **Technical Data Sheet**

# Adensa NVH 6013 Compound

Filled Heavy Layer Acoustic Barrier Compound

**Notes** 

Highland Adensa materials are high performance filled compounds formulated to meet a variety of OEM specifications. They are designed to be easy to process, and are available in more than 12 different off-the-shelf varieties.

Custom Adensa blends can also be formulated for your requirements.

Contact the Highland sales team to learn more at: contact@highlandplastics.com

#### Disclaimer:

The information contained in this document is for informational purposes only and should not be used as a substitute for testing to ensure that this product is suitable for its intended use. It is the sole responsibility of the user to determine the suitability of this product for the uses and applications intended by the user or others, to ensure compliance with all federal, state, and local laws, rules, and regulations, and to obtain all necessary certifications, permits, and authorizations. All products supplied by Highland Plastics, Inc. or any of its affiliates or subsidiaries are subject to Highland Plastics, Inc.'s terms and conditions of sale. Highland Plastics does not make, and expresssly disclaims, any warranty, express or implied, concerning the product, including the merchantability or fitness of the product for any particular purpose, or concerning the accuracy of any information provided herein. Nothing contained herein constitutes an offer for the sale of any product.

