

Adensa NVH 6012 Compound

Filled Heavy Layer Acoustic Barrier

Description Adensa 6012 is a low fog filled thermoplastic ethylene copolymer that provides acoustical sound barrier performance in automotive, construction, and industrial applications.

Applications Sheet and roll extrusion for NVH applications

Key Benefits

- Designed as an acoustic barrier, and formulated for thermoforming and die cutting
- Accredited to OEM standards, including GMW14171 and FMVSS 302
- Phthalate-free alternative to Mass Loaded Vinyl (Filled PVC)

Forms

- Pelletized compound
- 1,000 lb. container, 3' x 3' x 5'

Appearance Black

Typical Properties	Property	Nominal	Method
	Density	1.85 g/cc	ASTM D792
	Ash Content	74.8 %	ASTM D5630
	Tensile Strength, Br	249.2 PSI	ASTM D638
	Tear Strength, Br	98.5 lb-f/in	ASTM D624
	Elongation, Br	NB; >300%	ASTM D638
	Moisture Content	0.06 %	ASTM D6980
	Melt Index	2.86 g/10mm	ASTM D1238

Adhesion & Lamination Adensa 6012 is a polar material and can be extruded and laminated to most substrates without additional corona or flame treatment.

Processing Information	Extrusion	Value (English)	Value (SI)
	Extruding Temperature	360 - 400 °F	182 - 204 °C

Please contact your Highland Sales Representative to request regulatory information and safety data sheet.

Disclaimer:

The information contained in this document is for informational purposes only and should not be used as a substitute for testing to ensure that this product is suitable for its intended use. It is the sole responsibility of the user to determine the suitability of this product for the uses and applications intended by the user or others, to ensure compliance with all federal, state, and local laws, rules, and regulations, and to obtain all necessary certifications, permits, and authorizations. All products supplied by Highland Plastics, Inc. or any of its affiliates or subsidiaries are subject to Highland Plastics, Inc.'s terms and conditions of sale. Highland Plastics does not make, and expressly disclaims, any warranty, express or implied, concerning the product, including the merchantability or fitness of the product for any particular purpose, or concerning the accuracy of any information provided herein. Nothing contained herein constitutes an offer for the sale of any product.

Adensa NVH 6012 Compound

Filled Heavy Layer Acoustic Barrier

Notes

Highland Adensa materials are high performance filled compounds formulated to meet a variety of OEM specifications. They are designed to be easy to process and are available in more than 12 different off-the-shelf varieties.

Custom Adensa blends can also be formulated for your requirements.

Disclaimer:

The information contained in this document is for informational purposes only and should not be used as a substitute for testing to ensure that this product is suitable for its intended use. It is the sole responsibility of the user to determine the suitability of this product for the uses and applications intended by the user or others, to ensure compliance with all federal, state, and local laws, rules, and regulations, and to obtain all necessary certifications, permits, and authorizations. All products supplied by Highland Plastics, Inc. or any of its affiliates or subsidiaries are subject to Highland Plastics, Inc.'s terms and conditions of sale. Highland Plastics does not make, and expressly disclaims, any warranty, express or implied, concerning the product, including the merchantability or fitness of the product for any particular purpose, or concerning the accuracy of any information provided herein. Nothing contained herein constitutes an offer for the sale of any product.