



# Technical Data Sheet

## Komodo 3002 TPO

Soft-touch Black TPO

**Description** Komodo 3002 is a soft-touch TPO ideal for die-cut and automotive applications.

**Applications** Die-cut Class A parts

**Appearance** Black roll goods

Property	Nominal	Method
Hardness (Shore D)	27	ASTM D2240-15
Thickness	0.047in	Micrometer
Taber Abrasion	1.03mg	ASTM D4060-19
Tensile Strength (MD)	858psi	ASTM D638-22
Elongation at Break	NB; >300%	ASTM D638-22
Tensile Strength (AMD)	619psi	ASTM D638-22
Tear Strength (MD)	335 lb-f/in	ASTM D624-00
Tear Strength (AMD)	290 lb-f/in	ASTM D624-00
SG	0.903	ASTM D792-20

Tested on a 0.047" Sample

Please contact your Highland Sales Representative to request regulatory information and safety data sheet.

**Disclaimer:**

The information contained in this document is for informational purposes only and should not be used as a substitute for testing to ensure that this product is suitable for its intended use. It is the sole responsibility of the user to determine the suitability of this product for the uses and applications intended by the user or others, to ensure compliance with all federal, state, and local laws, rules, and regulations, and to obtain all necessary certifications, permits, and authorizations. All products supplied by Highland Plastics, Inc. or any of its affiliates or subsidiaries are subject to Highland Plastics, Inc.'s terms and conditions of sale. Highland Plastics does not make, and expressly disclaims, any warranty, express or implied, concerning the product, including the merchantability or fitness of the product for any particular purpose, or concerning the accuracy of any information provided herein. Nothing contained herein constitutes an offer for the sale of any product.



525 North 2nd Street  
Shepherd, MI 48883-9026

1-800-866-8208  
highlandplastics.com

Rev. 11/30/23